


BETA MAXI 'HI-LIFT'

Perfect for transferring thicker items



Digital controller



Increased clearance



'Normal mode' table



'Hi-lift mode' table

Features:

- Supplied with a 'Normal Mode' table and a 'Hi-Lift Mode' table.
- LED digital microprocessor control.
- Swing-head operation for clear view of working area.
- Safety release catch.
- Fingertip pressure control.
- LM6 cast aluminium construction for strength and durability.
- Self adhesive silicone base pad.
- Thermal cut out on the heating element if the temperature exceeds 235°C +/- 15°C.
- Manufactured and tested to comply with EC safety regulations. CE labelled.
- Lifetime heat element guarantee with 12 month warranty on machine.
- Full service/ spares support.
- Manual supplied illustrates electrical wiring diagram, exploded diagram and parts list.
- Full safety instructions

Machine Info:

Looking for that little extra, then look no further than the Beta Maxi 'Hi-Lift'!

Built to the same high specification as our market leading Beta Maxi press, which has led the way for over 25 years.

The machine is adapted for thicker items with the inclusion of a longer head post, that lifts the heat plate by approximately 2.5 cm (1 in) providing additional clearance between the heat plate and the base plate, which makes it possible to press onto thicker substrates. Safety remains paramount and the inbuilt thermal cut out on the heating element shuts off power to heating element should be the temperature exceed 235°C ± 15°C (455°F ± 27°F).

Ideal for use with flex, flock, laser, sublimation, bonding, laminating, reactivating and DTG.

Optional Tables:

15.3 cm x 15.3 cm, 20.5 cm x 20.5 cm
 25.4 cm x 25.4 cm, 30.5 cm x 30.5 cm
 30.5 cm x 15.3 cm, 38 cm x 15.3 cm
 38 cm x 38 cm, Umbrella table

Beta Maxi
'Hi-Lift'

Power consumption.....	2.5 kW
Power supply.....	230 Volts AC
Working temperature.....	70 - 235°C
Display timer range.....	0 - 9.59 min
Machine height open.....	65 cm
Machine height closed.....	35 cm
Machine width.....	51 cm
Machine width, loading.....	94 cm
Machine depth.....	89 cm
Machine depth, loading.....	120 cm
Work area required.....	92(W) x 64(H) x 110(D) cm
Weight export packed.....	52 Kg
Net weight.....	45 Kg
Press pad dimensions.....	38 cm x 50 cm
Fuse.....	12.5 A
A-weighted noise level.....	<70 dB(A)

Featuring the 'Hi-Lift' table and machine post for thicker items